



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 2 (replaces version 1)

Revision: 02.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· Trade name: **Signum universal bond II**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Application of the substance / the mixture** Dental bonding material

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

· **Informing department:** E-Mail: msds@kulzer-dental.com

· **1.4 Emergency telephone number:** Emergency CONTACT (24-Hour-Number): +49 (0)6132-84463

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 1B H360Fd May damage fertility. Suspected of damaging the unborn child.

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS02 GHS07 GHS08 GHS09

· **Signal word** Danger

· **Hazard-determining components of labelling:**

methyl methacrylate

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxo-5,12-diazahexadecane-1,16-diyl bismethacrylate

tert-butyl perbenzoate

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H360Fd May damage fertility. Suspected of damaging the unborn child.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

GB



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 2 (replaces version 1)

Revision: 02.07.2024

Trade name: Signum universal bond II

(Contd. of page 1)

· Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P273 Avoid release to the environment.
- P280 Wear protective gloves / eye protection.
- P280 Wear protective clothing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P405 Store locked up.

· Additional information:

Restricted to professional users.

· 2.3 Other hazards -

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Product based on methacrylates

· **Dangerous components:**

CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6	methyl methacrylate Flam. Liq. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥50-≤75%
CAS: 72869-86-4 EINECS: 276-957-5 Index number: 607-134-00-4 Reg.nr.: 01-2120751202-68-xxxx	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxo-5,12-diazahexadecane-1,16-diyl bismethacrylate Aquatic Chronic 2, H411 Skin Sens. 1B, H317 EUH204	25-50%
CAS: 75980-60-8 EINECS: 278-355-8 Index number: 015-203-00-X Reg.nr.: 01-2119972295-29-xxxx	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide Repr. 1B, H360Fd Aquatic Chronic 2, H411 Skin Sens. 1B, H317	1-<3%
CAS: 614-45-9 EINECS: 210-382-2	tert-butyl perbenzoate Org. Perox. C, H242 Aquatic Acute 1, H400 Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317 Aquatic Chronic 3, H412	≥0.1-<0.25%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- **After inhalation** Supply fresh air; consult doctor in case of symptoms.
- **After skin contact**
Instantly wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

(Contd. on page 3)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 2 (replaces version 1)

Revision: 02.07.2024

Trade name: Signum universal bond II

(Contd. of page 2)

- **After eye contact** Rinse opened eye for several minutes under running water. Then consult doctor.
- **After swallowing**
Rinse out mouth and then drink plenty of water.
In case of persistent symptoms consult doctor.
Product based on methacrylates
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
 - **Suitable extinguishing agents** CO₂, sand, extinguishing powder. Do not use water.
 - **For safety reasons unsuitable extinguishing agents** Water.
- **5.2 Special hazards arising from the substance or mixture**
Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
 - **Protective equipment:** No special measures required.
 - **Additional information** -

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).
- **6.4 Reference to other sections**
No dangerous materials are released.
See Section 8 for information on personal protection equipment.
-

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep containers tightly sealed.
 - **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
 - **Storage**
 - **Requirements to be met by storerooms and containers:**
Dry place, storage temperature <25 ° C
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:** Store container in a well ventilated position.

(Contd. on page 4)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 2 (replaces version 1)

Revision: 02.07.2024

Trade name: Signum universal bond II

· 7.3 Specific end use(s) No further relevant information available.

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

80-62-6 methyl methacrylate

WEL	Short-term value: 416 mg/m ³ , 100 ppm
	Long-term value: 208 mg/m ³ , 50 ppm

· DNELs

80-62-6 methyl methacrylate

Oral	general population, long term, systemic	8.2 mg/Kg (not defined)
Dermal	worker industrial, long term, systemic	13.67 mg/Kg/d (not defined)
	general population, long term, systemic	8.2 mg/Kg/d (not defined)
Inhalative	worker industrial, acute, local	416 mg/m ³ (not defined)
	worker industrial, long term, systemic	348.4 mg/m ³ (not defined)
	worker industrial, long term, local	208 mg/m ³ (not defined)
	general population, acute, local	208 mg/m ³ (not defined)
	general population, long term, systemic	74.3 mg/m ³ (not defined)

72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxo-5,12-diazahexadecane-1,16-diyl bismethacrylate

Oral	general population, long term, systemic	0.3 mg/Kg (not defined)
Dermal	worker industrial, long term, systemic	1.3 mg/Kg/d (not defined)
	general population, long term, systemic	0.7 mg/Kg/d (not defined)
Inhalative	worker industrial, long term, systemic	3.3 mg/m ³ (not defined)
	general population, long term, systemic	0.6 mg/m ³ (not defined)

75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Oral	general population, long term, systemic	0.0833 mg/Kg (not defined)
Dermal	worker industrial, long term, systemic	0.233 mg/Kg/d (not defined)
	general population, long term, systemic	0.0833 mg/Kg/d (not defined)
Inhalative	worker industrial, long term, systemic	0.822 mg/m ³ (not defined)
	general population, long term, systemic	0.145 mg/m ³ (not defined)

· PNECs

80-62-6 methyl methacrylate

freshwater	0.94 mg/l (not defined)
marine water	0.094 mg/l (not defined)
sewage treatment plant	10 mg/l (not defined)
sediment, dry weight, freshwater	10.2 mg/Kg (not defined)
sediment, dry weight, marine water	0.102 mg/Kg (not defined)

(Contd. on page 5)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 2 (replaces version 1)

Revision: 02.07.2024

Trade name: Signum universal bond II

(Contd. of page 4)

soil, dry weight	1.48 mg/Kg (not defined)
72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate	
freshwater	0.01 mg/l (not defined)
marine water	0.001 mg/l (not defined)
sewage treatment plant	3.61 mg/l (not defined)
sediment, dry weight, freshwater	4.56 mg/Kg (not defined)
sediment, dry weight, marine water	0.46 mg/Kg (not defined)
soil, dry weight	0.91 mg/Kg (not defined)
75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	
freshwater	0.0014 mg/l (not defined)
marine water	0.00014 mg/l (not defined)
sediment, dry weight, freshwater	0.115 mg/Kg (not defined)
sediment, dry weight, marine water	0.0115 mg/Kg (not defined)
soil, dry weight	0.0222 mg/Kg (not defined)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.

· **Breathing equipment:**

Not necessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

· **Hand protection**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.

Solvent resistant gloves

Check protective gloves prior to each use for their proper condition.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

GB



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 2 (replaces version 1)

Revision: 02.07.2024

Trade name: Signum universal bond II

(Contd. of page 5)

- **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**
 - Butyl rubber, BR
 - Nitrile rubber, NBR
- **Eye/face protection** Safety glasses
- **Body protection:** Light weight protective clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

- **Physical state** Fluid
- **Colour:** Colourless
- **Smell:** Ester-like
 - **Odour threshold:** Not determined.
- **Melting point/freezing point:** Not determined
- **Boiling point or initial boiling point and boiling range** 100 °C
- **Flammability** Not applicable.
- **Lower and upper explosion limit**
 - **Lower:** 2.1 Vol %
 - **Upper:** 12.5 Vol %
- **Flash point:** 10 °C (80-62-6 methyl methacrylate)
- **Auto-ignition temperature:** 430.0 °C
- **Decomposition temperature:** Not determined.
- **SADT** Not determined.
- **pH** Not determined.
- **Viscosity:**
 - **Kinematic viscosity** Not determined.
- **Kinematic viscosity**
 - **dynamic:** Not determined.
- **Solubility**
 - **Water:** Not miscible or difficult to mix
- **Partition coefficient n-octanol/water (log value)** Not determined.
- **Steam pressure at 20 °C:** 47 hPa
- **Vapour pressure:**
 - **Density and/or relative density**
 - **Density at 20 °C** 1.000 g/cm³
 - **Relative density** Not determined.
 - **Vapour density** Not determined.

9.2 Other information

No further relevant information available.

- **Appearance:**
 - **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
 - **Self-inflammability:** Product is not selfigniting.

(Contd. on page 7)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 2 (replaces version 1)

Revision: 02.07.2024

Trade name: Signum universal bond II

(Contd. of page 6)

· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures is possible.
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	
Highly flammable liquid and vapour.	
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
 - **Conditions to be avoided:** No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** None
 - **Additional information:**
If stored longer than recommended and/or above recommended temperature, product may polymerize generating heat.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
 - **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:		
80-62-6 methyl methacrylate		
Oral	LD50	~7,900 mg/kg (rat)

(Contd. on page 8)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 2 (replaces version 1)

Revision: 02.07.2024

Trade name: Signum universal bond II

(Contd. of page 7)

Dermal	LD50	>5,000 mg/kg (guinea pig) (OECD 402)
Inhalative	LC50/4 h	29.8 mg/l (rat)
72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxo-5,12-diazahexadecane-1,16-diy l bismethacrylate		
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide		
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
614-45-9 tert-butyl perbenzoate		
Oral	LD0	2,000 mg/kg (rat) (OECD 423)
Dermal	LD0	2,000 mg/kg (rat) (OECD 402)
Inhalative	LC0/4h	1.01 mg/L (rat) (OECD 439)
	LC100/4h	4.9 mg/L (rat) (OECD 439)

- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**
May damage fertility. Suspected of damaging the unborn child.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
 - **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
Repr. 1B

· **11.2 Information on other hazards**

· Endocrine disrupting properties	
128-37-0	2,6-di-tert-butyl-p-cresol

List II

SECTION 12: Ecological information

· **12.1 Toxicity**

· Aquatic toxicity:	
80-62-6 methyl methacrylate	
EC50/21d	49 mg/L (daphnia) (OECD 211)
EC50/48h	69 mg/l (daphnia) (EPA OTS 797.1300)
NOEC / 21d	37 mg/l (daphnia) (OECD 211)
ErC50 / 72 h	>110 mg/l (algae) (OECD 201)

(Contd. on page 9)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 2 (replaces version 1)

Revision: 02.07.2024

Trade name: Signum universal bond II

(Contd. of page 8)

NOEC / 72h	110 mg/l (algae) (OECD 201)
NOEC / 48h	48 mg/l (daphnia) (EPA OTS 797.1300)
EbC50 / 72h	>110 mg/l (algae) (OECD 201)
NOEC/ 35d	9.4 mg/L (fish) (OECD 210)
LC50/ 35d	33.7 mg/L (fish) (OECD 210)

72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate

EC50/48h	>1.2 mg/l (daphnia) (OECD 202)
LC50/96h	10.1 mg/l (fish) (OECD 203)
ErC50 / 72 h	>0.68 mg/l (algae) (OECD 201)
NOEC / 72h	0.21 mg/l (algae) (OECD 201)

75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

EC50/48h	10,100 mg/l (algae)
	3.53 mg/l (daphnia) (OECD 202)
LC50/96h	1.4 mg/l (fish) (OECD 203)
ErC50 / 72 h	>2.01 mg/l (algae) (OECD 201)
ErC10/72h	1.56 mg/L (algae) (OECD 201)

· 12.2 Persistence and degradability

80-62-6 methyl methacrylate

Biodegradation 94 % /14d (not defined) (OECD 301C)

72869-86-4 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate

Biodegradation 22 % /28d (not defined) (OECD 301B; ISO/ 9439/ EEC 92/69/V, C.4-C)

75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Biodegradation 0-10 % /28d (not defined) (OECD 301F; ISO 9408/ EEC 92/69/V, C.4-D)

· 12.3 Bioaccumulative potential

75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Bloconcentration factor (BCF) 47-55 (not defined)

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

· **12.7 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 2 (replaces version 1)

Revision: 02.07.2024

Trade name: Signum universal bond II

Disposal must be made according to official regulations.

(Contd. of page 9)

Uncleaned packagings:

Recommendation:

Disposal must be made according to official regulations.

Non contaminated packagings can be used for recycling.

SECTION 14: Transport information

14.1 UN number or ID number

· ADR, IMDG, IATA

UN1993

14.2 UN proper shipping name

· ADR

1993 FLAMMABLE LIQUID, N.O.S., special provision 640D (METHYL METHACRYLATE MONOMER, STABILIZED, 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate)

· IMDG

FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED, 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate), MARINE POLLUTANT

· IATA

FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED, 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate)

14.3 Transport hazard class(es)

· ADR



· Class

3 (F1) Flammable liquids.

· Label

3

· IMDG



· Class

3 Flammable liquids.

(Contd. on page 11)



Safety data sheet
according to 1907/2006/EC, Article 31


Printing date 29.07.2024

Version number 2 (replaces version 1)

Revision: 02.07.2024

Trade name: Signum universal bond II

(Contd. of page 10)

· Label	3
· IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant:	No Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user · Kemler Number: · EMS Number: · Stowage Category	Warning: Flammable liquids. 33 F-E, S-E B
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	-
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 12)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 2 (replaces version 1)

Revision: 02.07.2024

Trade name: Signum universal bond II

(Contd. of page 11)

· **UN "Model Regulation":**

UN 1993 FLAMMABLE LIQUID, N.O.S.
(METHYL METHACRYLATE MONOMER,
STABILIZED, 7,7,9(OR 7,9,9)-TRIMETHYL-
4,13-DIOXO-3,14-DIOXA-5,12-
DIAZAHEXADECANE-1,16-DIYL
BISMETHACRYLATE), 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 - **Directive 2012/18/EU**
 - **Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t**
 - **Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t**
- **15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H242 Heating may cause a fire.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H360Fd May damage fertility. Suspected of damaging the unborn child.
- H400 Very toxic to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH204 Contains isocyanates. May produce an allergic reaction.

· **Abbreviations and acronyms:**

SADT: Self Accelerating Decomposition Temperature
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Org. Perox. C: Organic peroxides – Type C/D
Acute Tox. 4: Acute toxicity – Category 4

(Contd. on page 13)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 29.07.2024

Version number 2 (replaces version 1)

Revision: 02.07.2024

Trade name: Signum universal bond II

(Contd. of page 12)

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

Repr. 1B: Reproductive toxicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**

GB